DECLARATION OF PERFORMANCE

30805/2021 **BTT 25**

1- Unique identification code of the product-type:

BTT 25

30805/2021 2- Number of type:

3- Intended use of construction product, in accordance with UNI EN 15650:2010 - Ventilation for buildings - Fire dampers:

IN ASSOCIATION WITH PARTITIONS IN ORDER TO KEEP THE FIRE COMPARTMENTS IN INSTALLATION FOR HEATING, VENTILATION AND AIR-CONDITIONING

4- Name and address of manifacturer:



Brofer S.r.l.

31023 - Resana (TV)

6- System of assessment and verification of constancy of performance of construction product:

1

7- Notified body:

CSI spa 0497

Issued the certificate of constancy of performance of the product on the basis elements:

- i) determination of the product-type on the basis of type testing (including sampling), type calculation, tabulated values or to descriptive documentation of the product
- ii) initial inspection of factory and of factory production control
- iii) continuous surveillance, assessment and evaluation of factory production control
- 9- Performance declared

ESSENTIAL REQUIREMENT		RESULT	STANDARD	
Nominal activation conditions-sensitivity	Sensing element response temperature	Pass	UNI EN 15650:2010	
	Sensing element load capacity	Pass		
Response delay (response time) in closure		Pass		
Durability of operation reliability		Pass		
Recistance to fire				

Resistance to fire

Integrity (E)	with manual device on wall:El 180 (Ve i - o)S with manual device on light wall: El 120 (Ve i-o)S	
Insulation (I)	with manual device on slab: EI 120 (Ho Ve i-o)S with motorized device on wall:EI 120 (Ve i - o)S with motorized device on light wall: EI 120 (Ve i-o)S with motorized device on slab: EI 120 (Ho Ve i-o)S	
Smoke leakage (S)		UNI EN 15650:2010
Mechanical stability (in E)	Pass	
Maintenance of cross section (under E)	Pass	
Durability delay (response time) in closure	Pass	
Durability of operational reliability	Manual device - 300 pass	
Durability of operational reliability	Motorized device - 10200 pass	

10- The provision of the product referred to in paragraphs 1 and 2 is consisted with the declared performance in point 9 The declaration of performance under the only responsability of the manufacturer referred to in point 4 Signed in the name and on behalf of the manufacturer Il legale rappresentante

GianTuca/Brotto

11-11-21

Resana





31023 - Resana (TV) **ITALIA**

Standard: UNI EN 15650:2010

Unique identification code of the product-type: BTT 25

Number of type: **30805/2021**

Notified body: 0497

IN ASSOCIATION WITH PARTITIONS IN ORDER TO KEEP THE FIRE COMPARTMENTS IN INSTALLATION FOR HEATING, VENTILATION AND AIR-CONDITIONING

	<u> </u>			
ESSENTIAL REC	QUIREMENTS	RESULT		
Nominal activation conditions-sensitivity	Sensing element response temperature	Pass		
	Sensing element load capacity	Pass		
Response delay (response time) in closure		Pass		
Durability of operation reliability		Pass		
Resistance to fire				
Integrity (E) Insulation (I) Smoke leakage (S)		with manual device on wall:EI 180 (Ve i - o)S with manual device on light wall: EI 120 (Ve i-o)S with manual device on slab: EI 120 (Ho Ve i-o)S with motorized device on wall:EI 120 (Ve i - o)S with motorized device on light wall: EI 120 (Ve i-o)S with motorized device on slab: EI 120 (Ho Ve i-o)S		
		Pass		
Mechanical stability (in I	E) 	1 433		
Maintenance of cross section (under E)		Pass		
Durability delay (response time) in closure		Pass		
Durability of operationa	l reliability	Manual device - 300 pass		
Durability of operational reliability		Motorized device - 10200 pass		